

# ComNav<sup>®</sup>

New



## G7

### High Precision GNSS

1 cm Position, 0.01° Heading Capable

## Smart RTK Receiver Base Station or Rover

- Professional RTK receiver suitable for AGVs, agricultural, machine control, construction, mining, automated positioning, and scientific applications
- Multi-frequency Multi-GNSS Constellations
- GPS, GLONASS, BeiDou, Galileo, QZSS and SBAS
- Dual marine grade antenna for precise heading calculations
- Built-in web user interface for secure config., data retrieval and upgrades
- Built-in 3G cellular network modem global coverage
- Built-in network and UHF SATEL radio modules
- Advanced low noise, multi-path mitigation technology coupled with high dynamic response
- Wi-Fi, Bluetooth, Ethernet and other Serial communication ports
- GNSS L Band Trimble RTX / OmniSTAR correction service compatible
- Rugged industrial grade, sealed to IP67 rating
- Excellent for Static and Dynamic applications
- Data updates selectable 1 to 50 Hz
- NMEA 0183 interface
- FCC and CE certified
- 2 year warranty
- Worldwide service



### Wind Farm Support



### Cable Laying



#### GNSS CAPABILITIES

Multi-frequency GNSS all in view simultaneously tracked satellites

<b>GPS:</b>	L1C/A, L2C, L2E, L5
<b>GLONASS:</b>	L1C/A, L2C/A, L3 CDMA
<b>Galileo:</b>	E1, E5A, E5B, E5AltBOC, E6
<b>BDS:</b>	B1, B2, B3
<b>QZSS:</b>	L1 C/A, L1 SAIF, L2C, L5, LEX
<b>SBAS:</b>	L1 C/A, L5, WAAS, MSAS, EGNOS
<b>L Band</b>	OmniSTAR VBS, HP and XP

#### GNSS PERFORMANCE (RMS)\*

	Horizontal	Vertical
<b>RTK:</b>	8 mm + 1 ppm	15 mm + 1 ppm
<b>DGPS:</b>	25 cm + 1 ppm	50 cm + 1 ppm
<b>SBAS (WAAS):</b>	0.5 m	0.85 m
<b>Heading Accuracy:</b>	< 0.3° @ 0.5 m antenna separation	
	< 0.1° @ 1.0 m antenna separation	
	< 0.06° @ 2.0 m antenna separation	
	< 0.02° @ 5.0 m antenna separation	
	< 0.01° @ 10.0 m antenna separation	

<b>Pitch/Roll Accuracy:</b>	< 0.01° @ 5.0 m antenna separation
<b>Heave Accuracy:</b>	30 cm DGPS, 10 cm RTK
<b>Initialization Time:</b>	< 10 s typical
<b>Initialization Reliability:</b>	> 99.9% Timing
<b>(1 PPS) Accuracy:</b>	50 nsec
<b>Rate of Turn:</b>	90°/sec max.
<b>Maximum Speed:</b>	1,850 kph
<b>Maximum Altitude:</b>	18,288 m

#### ENVIRONMENTAL

<b>Operating Temp:</b>	-40°C to 75°C (-40°F to 167°F)
<b>Storage Temp:</b>	-55°C to 85°C (-67°F to 185°F)
<b>Humidity:</b>	Up to 100%
<b>Waterproof / Dustproof:</b>	IP67
<b>Shock Resistance:</b>	1 m (3.28 ft) fall onto concrete
<b>Vibration:</b>	Mil-STD-810G
<b>Tilt Sensor:</b>	e-Bubble leveling

#### MECHANICAL

<b>Dimensions (L x W x H):</b>	160mm x 120mm x 56mm 6.4 in x 4.7 in x 2.2 in less
<b>Weight:</b>	than ≤ 1.2kg (2.6lb)

#### COMMUNICATIONS AND DATA RECORDING

<b>Connectors I/O:</b>	1 x 19 pin aviation plug ( 1 x Power, 1 x RJ45, 1 x CAN, 2 x RS232, 1 x SMA) 1 x TNC (Radio) 1 x mini-USB (firmware upgrade) 1 x TNC GNSS1 1 x TNC GNSS2 1 x TNC (4G Antenna) 1 x mini-USB (firmware upgrade) 1 x TNC antenna connector (internal radio)
<b>Data Recording:</b>	Web UI Data Collection Management Software via smart phone (Android optional)
<b>Network Modem:</b>	4G Internal modem cellular global coverage
<b>Wi-Fi:</b>	Integrated module w antenna 802.11 b/g/n, access point mode
<b>Bluetooth:</b>	Internal multimode system compatible w Android, Windows Mobile and Windows desktop OS
<b>UHF Radio:**</b>	Frequency range, 403 - 473 MHz
<b>Data Update Frequency:</b>	Selectable 1, 2, 5, 10, 20, 50 Hz Position and Heading Output
<b>Baud Rates:</b>	1200 to 460800
<b>LAN Network:</b>	HTTP, HTTPS, TCP/IP, UDP, FTP NTRIP Caster, NTRIP Server, NTRIP Client Simultaneously transmits multiple data stream Supports proxy server and route table Supports UDNp ad Zeroconf Supports Email alerts & position monitoring Event marker input
<b>Protocols:</b>	NMEA 0183 v2.x, v4.x (position and heading) RTCM 2.x, RTCM 3.x, input and output NTRIP Client, NTRIP Caster
<b>Web User Interface:</b>	Secure; Allows remote configuration, data retrieval and firmware updates; multiple streaming/ ports

#### POWER

<b>Input Voltage:</b>	9 to 36 VDC
<b>Power Consumption:</b>	4.3 W normal

#### CERTIFICATIONS AND CALIBRATIONS

FCC Part 15 (class B Device), FCC Part 22, 24, 90;  
CE IEC60945, Bluetooth EPL, IGS and NGS Antenna calibration MIL-STD-810G, IEC68-2-27

#### DUAL ANTENNA OPTIONS (included)

Dual Marine IP68 w marine mobile 1" dia thread mounts (standard) Dual Geodetic IP65 w land mobile 5/8" dia. mounts (optional)

\* Accuracy and reliability specifications may be effected by multipath, satellite geometry and atmospheric conditions. Performance assumes minimum of 5 satellites, coupled with the follow up of recommended general GNSS practices.

\*\* UHF type approvals are country specific

Represented by:



# ComNav®



ComNav Marine Ltd.  
#15-13511 Crestwood Place,  
Richmond, British Columbia • Canada • V6V 2G1  
Phone: 604-207-1600 • Fax: 604-207-8008  
E-mail: sales@comnav.com

**www.comnav.com**  
**Worldwide Service**

Printed in Canada

Specifications subject to change without notice

August 2018